

SUPER SELLETTES 2

EXCEPTIONALLY ADHESIVE GREASE



RANGE OF GREASE

NLGI 2
HIGH LOADS
WATER RESISTANT
ADHESIVE

Grade
2

-10°C/+120°C

APPLICATIONS

Heavy load couplings

Extreme pressure level

APPLICATIONS

SUPER SELLETTES 2: thanks to its exceptional adhesiveness, it can be used in extreme conditions such as those subject to heavy truck couplings.

SUPER SELLETTES 2 can be used when the vehicle is undergoing a major wash or is working in water.

Unleaded grease particularly suited not only for the lubrication of fifth wheel couplings but also for racks, drill bit screws (TP) or drill pipe threads.

BENEFITS

- Extreme pressure, thanks to innovative tin technology (same family as lead but harmless).
- Totally insoluble in water, even at boiling point or steam
- Exceptional adhesiveness to metal
- High resistance to distortion and shearing

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Colour	-	Visual	Black
Type of soap	-	-	Li/Ca
Consistency	NLGI grade	NF T 60-506	2
Penetration 60 strokes at 25°C	1/10 mm	NF T 60-132	265/295
Base oil viscosity at 40°C	mm ² /s	ASTM D 7152	1032
Dropg point	°C	NF T 60-102	> 170
Spray off	%	ASTM D 4049	15
Wash out at 79°C	%	ISO 11009	< 5
4-ball wear	mm	ASTM D 4172	< 0.5
4-ball welding	kg	ASTM D 2596	> 500
Temperature range	°C	-	-10 / +120

The above data are provided on an indicative basis only.

HEALTH, SAFETY AND ENVIRONMENT

Disposal must be carried out in compliance with the rules governing the disposal of used lubricants.

Must be stored away from bad weather.

For further details, our Technical Department is available to assist you.